A Unified Framework For Data Integrity And Security In Big Data: Leveraging Clustbigfim And Blockchain

V. Vincent Arokiam Arul Raja[1], Dr. C. Senthamarai[2]

[1]Lecturer, Dept. of Computer Science, Government Arts College, Salem 7, Tamilnadu, India
[2]Assistant Professor, Dept. of Computer Application, Govt Arts College, Salem 7, Tamilnadu, India

Abstract:
Large datasets from various fields raise concerns about security, reliability, and consistency. While centralized databases facilitate data storage, transmission, processing, and access, ensuring security and safe storage is crucial to prevent malicious attacks. Blockchain technology is increasingly being utilized to enhance data security in big data systems. As a distributed digital ledger, it addresses the issues of data duplication and vulnerabilities across networks. Blockchain offers fault tolerance, ensuring secure data handling. It also allows for controlled access without compromising data integrity in distributed systems. Specifically, the technology focuses on agreement, authentication, and auditing of data access. To improve data processing, techniques such as collaborative filtering (CF) and MapReduce with Frequent Itemset Mining (FIM) are employed. CF identifies relationships and similarities among frequently occurring items, thereby enhancing processing accuracy and efficiency. MapReduce streamlines the FIM process by distributing the workload, which reduces processing time. FIM helps manage combinatorial complexity and mitigates risks associated with vulnerabilities and data manipulation. Throughout these processes, security is prioritized at every stage. Techniques like classifier algorithms, class balancing, and filter association algorithms are utilized to ensure robust security throughout the data handling pipeline. Together, these methods aim to provide strong security for big data through the use of consensus and distributed ledger technology.

Keywords: BlockChain Algorithm (BCA), Collaborative Filtering (CF), Map Reduce Function (MRF), Frequent Itemset Mining (FIM), ClustBigFim (Cluster Bigdata FIM), Classifier algorithm, Class balancer, and Filter Association Techniques.

1. INTRODUCTION

The rapid growth of information technology has led to an explosion of heterogeneous data, exceeding traditional data processing capabilities. This "big data" era presents both opportunities and challenges. The diverse sizes and formats of data from various applications demand more adaptable processing tools and platforms.

Many modern big data solutions rely on cloud computing, which offers cost-effectiveness, reliability, scalability, and distributed computing capabilities. However, cloud adoption introduces data management, security, and privacy challenges, including data ownership, multi-tenancy, and access control, as users don't directly own the infrastructure.

Blockchain technology offers a solution by distributing metadata into a secure, decentralized database. Each block in the blockchain contains transaction records and block information, secured by cryptographic hash functions. These hashes validate data within blocks, and consistent hashes allow blocks to join the chain. All blockchain operations are recorded as auditable transactions, providing proof of ownership. This addresses security concerns related to authorized access to centralized data and helps detect malicious activities and prevent data duplication.

MapReduce (MRF) manages the execution phases of data processing, distributing computation for consistency and efficiency. It facilitates the analysis of diverse data elements to create hierarchical models. Pre-processing steps enhance reliability and integrity, and the system supports record management without

compromising data integrity or security. Frequent Itemset Mining (FIM) optimizes data organization and mitigates risks associated with data manipulation, maintaining database consistency.
Collaborative Filtering (CF) is applied to blockchain data to identify user preferences and similarities based on consensus relationships. This can vary depending on the specific consensus mechanism used. By analyzing user behavior and potential item ratings, CF improves processing efficiency and performance metrics. The overall focus is on maintaining efficiency, integrity, reliability, accuracy, and security in big data management within the digital record system. Integrating these methods offers a robust solution for enhancing security in big data systems.

2. RELATED WORKS

Seo et al (2018) have declared that the acknowledgment of range detecting is turning out to be more also, more conceivable with the advancement of advances, for example, man-made consciousness and programming radio. While it has to pay regard for its presentation, it can't overlook the security issues it faces. It has been proposed an advancement plan to guard against range detecting data adulteration (SSDF) assaults in light of the twofold limit energy discovery and square chain innovation [1].
Puppala et al (2016) have uncovered that the medical care administrations industry is consistently giving indications of progress and supporting new headways and progresses. One of the transcendent necessities in the present medical care frameworks is to secure the patient's clinical report against likely aggressors. Subsequently, it is fundamental to have secured data that can simply support individuals can get to the patient's clinical report [2].

Tranieri et al (2013) have point by point that Cardiovascular autonomic neuropathy (CAN), one of the significant confusions in diabetes, whenever recognized at the subclinical stage takes into account viable treatment and staying away from additional complexity including cardiovascular pathology. Surface ECG (Electrocardiogram)- based conclusion of CAN is helpful to defeat the restriction of existing cardiovascular autonomic reflex tests customarily utilized for CAN distinguishing proof in clinical settings [3].

Victoria et al (2016) have declared that the ton of archives that are kept up with by mediators just to guarantee the legitimacy and uprightness of the archives. There is a ton of assets put in for upkeep reasons yet the vast majority of the time the framework neglects to convey what is guaranteed. With the approach of Blockchain innovation, it can help the specialists to keep up with it [4].
Mohamed Tahar et al (2018) have uncovered that the IoT plays a critical part in our each day timetable and it incredibly influences us. Central security objectives like classification, respectability, and accessibility are significant difficulties in IoT because of their distributive nature and monstrous scale. The decentralized methodology utilized in BC would make a more dependable framework for gadgets, to run on by killing weak links. Diverse cryptographic calculations utilized in blockchains, would bring about more noteworthy security of purchaser data [5].
Zhonglin Chen et al (2018) has point by point that the super thick organization (UDN) is perhaps the most encouraging advancements in the fifth era (5G) to address the network framework limit issue. In any case, it is another test that the client equipment（UE） secure access UDN made out of the passageways (APs) which described with self-rule, impermanent and dynamic. In 5G UDN, the APs are autonomous and equivalent. The UDN can be viewed as a decentralized admittance organization [6].
Tipping et al (2011) have declared that the RVM empowers meager characterization and relapse capacities to be gotten by directly weighing few fixed premise capacities from a huge word reference of potential candidates.TOA on RVM has O(M3) time and O(M2) space intricacy, where M is the preparing set size. It is accordingly computationally infeasible on exceptionally enormous data collections which are proposed CBA [7]. Simon Fraser et al (2014) have uncovered that the utilization of computerized applications is on the ascent these days. So the preparation of that data is finished by a device called MapReduce. MapReduce has its construction that can't be adjusted. While preparing that data, the slant will happen in both guides and lessen the stage. Guide slant is not difficult to diminish yet, if there should arise an occurrence of decreased stage it might require some investment to diminish it [8].
Satoshi Nakamoto et al (2017) have point by point that the Production network Management frameworks give data sharing and investigation to organizations and backing their arranging exercises. They are not founded on genuine data because there is lopsided data between organizations, then, at that point driving to aggravation of the arranging calculations [9]. Marzouki et al (2017) has declared that the research has proposed another

encoding strategy roused from the square chain innovation, by which an activity arrangement data and the comparing machine data is incorporated in an activity hub and connections all activity hubs to frame an activity list with pointer innovation of C++ program language [10].

Manikandan D, Valliyammai C, Karthika RN (2020) et.al decides the security handling to assist with working on the data in the blockchain of the digital currency and time. It forestalls data altering, and confirmation issues while getting to the unified workers. It helps to zero in on distributed storage and the executives for security-improving by sidestepping the malignant clients. By utilizing the SWOT (Strength Weakness Opportunities Threats) investigation to perform and tending to the benefits and innovation advancements in blockchain calculation [11]. S. Dhanalakshmi, G.Charles Babu (2019) et.al portrays the bitcoin innovation for crypto-currency exchanges in digitized, decentralized, trusted, and got in the circulated record. Each exchange has been confirmed by the hashing algorithm alongside a gigantic measure of data. It covers the defects of capacity in digital money and gives the elements of the condition of the cycle, attributes, applications associate with enormous data investigation while utilizing the BlockChain calculation [12]. It assists with working on the connection between digital money, security, adaptability to decentralization alongside straightforwardness. Besides, it has been displayed as a huge data insightful structure to find the cycle of bitcoins.

Alex. R. Mathew (2019) et.al portrays the digital money adjust to businesses, finance, and so on To find the cycle alongside digital protection by utilizing Blockchain methods in huge data. To examines this advancement under 30 scientists. Blockchain algorithms along with IoT, Networks, and data discriminate the versatile and improve the efficiency in security management. The solutions from uniformity while examining the existing and proposed techniques in the future [13].Dong Wang, Huanjuan Wang, and Yuchen Fu (2021) et.al depicts the security of the slat and controlling ability in huge data while examining the working progress alongside the IoT and brilliant network. It joins to gives the gigantic response while getting to the 5G MEC at the edge of the 5G organization framework. It gives dependability and precision by utilizing blockchain calculation. It sent the MEC entryway/Server. It concentrates to recognize the weaknesses by utilizing PoW, PoS, DPoS, PDFT to play out the distinctive agreement of normal registering time and understanding point of view [14].

Swagatika Sahoo, Rishu Roshan, Vikash Singh, and Raju Halder are still up in the air business development as the main thrust and increment the adaptation of the promoting field the other way around. Yet, the dangers that have happened while entering the data-driven situation convey inclined to different intimidations. It was overwhelmed by utilizing the BDmarks of watermarking to build the adaptation and stay away from the dangers inside and outside, increment the security products for business development [15].

3. METHODOLOGY:



Fig 3.1: Security Management by using Blockchain along with ClustBigFim

ClustBigFim strategy applied on Map Reduces programming model. In this clustering technique, batching using Blockchain computation to make Clusters from massive datasets to mine ceaseless itemsets from created clustering using Map Reduce programming model. The execution efficiency of the Collaborative screening

estimation is extended by applying the k suggests covered computation as one of the pre-processing strategies. CF computation reliant upon Map Reduce programming model bright lights on pre-planning, persistent itemsets of size k is mined using ClustBigFim and Blockchain estimation and discovered perpetual thing sets CF works on enormous datasets with extended execution capability using Map Reduce.

A. Collaborative clustering

It has been used by some recommender structures. Communitarian isolating has two distinguishes, a slender one and a more expansive one. When in doubt, local area arranged to isolate is the way toward filtering for data or models using techniques including facilitated exertion among various trained professionals, points of view, data sources, etc Utilizations of the local area situated isolating typically incorporate extraordinarily colossal educational assortments. In data mining, kth Node gathering is a procedure for bundle assessment that intends to allocate discernments into k packs in which each insight has a spot with the pack with the nearest mean. The issue is computationally inconvenient, in any case, there are useful heuristic estimations that are typically used and meet rapidly to a local ideal.

$r_{u,i} = aggr_{u^1 \in U} r_{u^1,i}$ …… (1)

Collaborative filtering (CF) strategies use a database of user preferences to preAdd additional topics or items that a new user may like. In a typical CF scenario, there is a list of (m) users (u_1, u_2, u_m....,) and a list of (n) items {i_1, i_2, i_n). Each user (u_i) has a list of items (I_{u_i}) that the user has rated, or from which their preferences have been inferred through their behaviour. The ratings can be either explicit, such as scores on a 1 to 5 scale, or implicit, such as purchases or click-throughs.

$r_{u,i}$ = $\frac{1}{N}\sum_{u^1 \in U} r_{u^1,i}$n …… (2)

To assess collaborative filtering calculations, we utilize measurements based on the types of CF applications. Rather than arrangement error, the most commonly used assessment metric for predictive performance in CF is the Mean Absolute Error (MAE). MAE is used to predict the error within a fixed boundary, focusing on the differences between predicted values. It considers the average magnitude of errors without regard to their direction.

$.\frac{1}{x}\sum_u (xi - x)$ ……(3)

In addition to MAE, accuracy and recall are general metrics used for ranking items in information retrieval research. Here, it is important to highlight several commonly used CF metrics: Mean Absolute Error (MAE), Mean Squared Error (MSE), Root Mean Squared Error (RMSE), and Receiver Operating Characteristic (ROC) sensitivity. Instead of focusing solely on arrangement accuracy or clustering error, the predominant measurement in CF research literature is still the Mean Absolute Error (MAE), which calculates the average of the absolute differences between predictions and actual ratings.

Table 3.1: Big Data Analysis

S.NO	Map Reduce	Pig	Hive
1.	Powerful and Parallelism	Data-flow Language	SQLish Language
2.	Procedural Structure	Programmer's and researchers	Analyst for generating reports.

B. MapReduce Overview

The MapReduce model divides the computation process into two stages: the map stage and the reduce stage. The map function, written by the user, takes a set of input key/value pairs and generates a set of output key/value pairs. The MapReduce library collects all the intermediate values associated with a specific intermediate key and passes them to the reduce stage. In the reduce stage, the function, also created by the user, takes an intermediate key and a set of values associated with that key. It combines these values to produce

a potentially smaller set of output values. Typically, the reduce function generates either no output value or just one output value per invocation.

C. Cluster Analysis

Clustering is used to identify information objects that are similar to each other. The similarity can be determined based on various factors relevant to specific needs, such as purchasing behavior, responsiveness to certain actions, geographical locations, and more. For example, an insurance company can group its clients based on criteria such as age, home location, income, and so forth. This clustering of data is useful for developing strategies aimed at understanding clients better and consequently providing more tailored services.

- ***Nearest neighbor strategy:*** This is a technique that classifies each record in a given dataset by examining a combination of classes and the methods involved in determining the k records that are most similar to it from a historical dataset (where $k \geq 1$). This method is often referred to as the k-closest neighbor technique.

D. Prediction

A prediction is a statement about how events are expected to unfold in the future, often based on experience or data. While there is considerable overlap between prediction and estimation, a prediction may denote that a specific outcome is anticipated, while an estimate may encompass a range of potential outcomes. Although absolute certainty about the information is generally unattainable, predictions are vital for enabling planning regarding possible developments.

E. Confidentiality

Confidentiality is an ethical standard associated with various professions. In ethics, as well as in certain legal contexts and alternative forms of legal resolution like mediation, certain types of communication between an individual and a professional are considered "privileged" and may not be discussed or disclosed to outsiders.

i) CLUSTBIGFIM and BLOCKCHAIN

CLUSTBIGFIM is used to access three main processes: MRF, CF, and FIM, along with the BCA techniques to enhance efficiency and performance in real-world applications. It is essential to utilize the CB (Class Balancer) feature to avoid data duplication and unnecessary information. Additionally, this tool helps manage memory usage effectively and facilitates access to consented data. To further improve efficiency identification within the Gaussian process, classifiers such as ZeroR, JRIP, and EM can be added. This aids in reducing uncertainty within the Bayesian framework of the Gaussian process. It also conducts regression and classification tasks among different datasets and recognizes complex non-parametric functions within a distributed system.

Collaborative filtering algorithms often require

- Neighborhood-based Approach
- Model-based Approach
- Hybrid Approach

The following methodologies are primarily used to identify malicious clients accessing data. They aid in addressing both the user and the account holder within the distributed system's functionality. A classifier is employed to separate the functionalities in a block-wise manner. Even if uncertainty arises, the BC algorithm is utilized to predict and eliminate the influence of malicious clients.

ii) STEPS OF EXECUTION PROCESS

Stage 1: The first stage of Collaborative Filtering involves calculating the client's historical profile, which can be represented as a rating matrix. In this matrix, each row corresponds to a user, each column represents specific items, and the value at the intersection of a row and a column reflects the user's rating for that item. If there is no rating value at this intersection, it indicates that the user has not rated that item yet. Due to the challenge of sparse ratings, we use a list to replace the matrix.

Stage 2: The next step is to compute the similarity among users to identify their closest neighbors. Various similarity measurement techniques exist, with the Pearson correlation coefficient being the most widely used as a benchmark for Collaborative Filtering (CF). Additionally, the Cosine similarity measure is calculated using the following formula:

$$\text{Sim}(x,y) = \frac{\sum_{s\in Sxy} r_{x,s} r_{y,s}}{\sqrt{\sum_{s\in Sxy} r_{x,s}^2}\sqrt{\sum_{s\in Sxy} r_{y,s}^2}} \quad \ldots\ldots\ldots\ldots\ldots\ldots\ldots\ldots\ldots\ldots\ldots\ldots\ldots (4)$$

In the context of this analysis, let (r_x) represent the rating given by client (x) on a specific item (s), and (r_y) represent the rating given by client (y) on the same item (s). The notation (S(x)(y)) indicates the items that both client (x) and client (y) have evaluated together.
The next step involves calculating the overall rating for the item. This rating is determined by taking a weighted average of the evaluations provided by the neighbouring clients, as described in Equation 4.
Additionally, (r_x) signifies the normalised rating of client (x), which can be referenced in Equation 5.

$$r_{x.s} = \vec{r_x} + \frac{\sum_{y\in S_{xy}}(r_{y,s} - \vec{r_x})sim(x,y)}{-\ \sum_{y\in S_{xy}} sim(x,y)} \quad \ldots\ldots\ldots\ldots\ldots\ldots\ldots\ldots\ldots\ldots\ldots\ldots\ldots\ldots\ldots\ldots\ldots (5)$$

The calculation process of the Collaborative Filtering algorithm can be very demanding in terms of computing time and resources. When dealing with a large dataset, the computations may take several hours or even longer. To address this issue, we propose a new method that implements the Collaborative Filtering algorithm on the blockchain.

Features	**MapReduce**	**Pig**	**Hive**
Language	Algorithm of Map and Reduce Functions (Can be implemented in C, Python, Java)	PigLatin (Scripting Language)	SQL-like
Schemas/Types	No	Yes (implicit)	Yes(explicit)
Partitions	No	No	Yes
Server	No	No	Optional (Thrift)
Lines of code	More lines of code	Fewer (Around 10 lines of PIG = 200 lines of Java)	Fewer than MapReduce and Pig due to SQL Like nature
Development Time	More development effort	Rapid development	Rapid development
Abstraction	The lower level of abstraction (Rigid Procedural Structure)	Higher level of abstraction (Scripts)	Higher level of abstraction (SQL like)
Joins	Hard to achieve join functionality	Joins can be easily written	Easy for joins
Structured vs Semi-Structured Vs Unstructured data	Can handle all these kinds of data types	Works on all these kinds of data types	Deal mostly with structured and semi-structured data
Complex business logic	More control for writing complex business logic	Less control for writing complex business logic	control for writing complex business logic
Performance	A fully tuned MapReduce program would be faster than Pig/Hive	Slower than fully tuned MapReduce program, but faster than badly written MapReduce code	Slower than fully tuned MapReduce program, but faster than badly written MapReduce code

Table 3.2: ClustBigFim and BlockChain characteristics

The CB-Class Balancer demonstrates a method for addressing data imbalance when working with large datasets. This process typically involves undersampling the majority class to achieve a balanced distribution. The aim is to eliminate bias in data processing.

To organise the datasets from the database, examples should be arranged based on the count of occurrences. To address the minority class, it may be necessary to either increase its sample size or identify the rarer instances within the majority class. This issue can be effectively managed by employing classification algorithms or adjusting the classes in training datasets, which helps to enhance data integrity.Required steps to access the class balancer are,

- Metrics to the training datasets
- Resample.
- Cross-validation till k^{th} node.
- To apply ensemble techniques.
- Collect samples from different ratios.
- Refine to the abundant class.
- Execute the updated datasets.

These processes are designed to ensure data consistency. Additionally, they help eliminate bugs when accessing and updating modelling datasets. They are used to describe fraud identification while accessing, recovering, and manipulating data in a centralised system. This approach helps maintain data security and monitors the approval of activities.

$$r_{u,i} = k \sum_{u^1 \in U} simil(u, u^1) r_{u^1,i} \quad \text{..... (5)}$$

The weight of the data, as shown in Equation 5, is essential for recognising the patterns in beverage consumption. This weight helps determine the balance and relationships between different events. Additionally, it allows for the elimination of incomplete information without undermining the methods and systems designed for the performance series. It is also recorded once it controls the refined handling based on tendencies that may follow either a parallel or sequential development of the training datasets, or both. The approach does not rely solely on grid or factorisation methods, as it continues to monitor changes over time. This ongoing screening aims to maintain simplicity while identifying hidden elements within a scattered structure.



Fig 3.2: Class balancer – Applying hybrid approaches

Classifier Techniques:

- ***Predictors:*** To foresee the standard extraction of the extent contrarily in the Nyquist pace of the techniques. It decides the pattern elements of the greater part classification of the exhibition as a benchmark in the execution. It depends on the given objective met to the indicators of the variable through the isolation.

$r_{u,i}$ = r_u^- + k $\sum_{u^1 \in U} simil(u, u^1)(r_{u^1,i} - r^-_{u^1})$ ..... (6)

In (Equ 6) looks at the significant comparability the assortments of preparing datasets characterize to the adjusting factors. The strategies applied to gathers the various results which are a match or obscure factors order to identify the greater part. It portrays the heuristic to create the fresh debuts of the info planning to refresh the qualities and observing to following the likeness in the middle of the course of indicators.

- **JRIP (RIPPER) – Repeated Incremental Pruning to Predictive Error Reduction:** It discovering the solicitation for the classification methodologies. It utilizing the standard-based class list which recognizes the botches and disposes of them to extend the show reasonability under the creating, pruning, Optimizing, and assurance measure. It updates the refining of the bungle distinguishing proof and changes the characteristics again reset to executing the datasets gathering.
- **EM – Expectation Maximization:** To decides the probability of the expansion in logarithm from the grouping datasets. It appraises the maximum, min which relies on the emphasis iteration of the field data. To advance the emphasis to noticed the stochastic inert factors under the process elements of the centroid. It separates into two stages which are H-Hypotheses for the probabilistic task and M-update the refining task of the latent variables.

K = 1/ $\sum_{u^1 \in U} |simil(u, u^1)| and\ r_u^-$ ..... (7)

Since the (Equ 7) depends on recognizing the maximum in the latent factors according to distinguishing the laws and updating hypotheses speculations which are logarithms. It controls to enhance the accuracy for time concern to expand the exactness of outcomes while accessing the verification and validation. It verifies to apply them EM to produced the optimal storage functionality with no redundancy.

- **Gaussian Process - GP:**

Simil(x,y)= $\frac{\sum_{i \in l_{xy}} (r_{x,i} - r_{\bar{x}}^-)(r_{y,i} - r_{\bar{y}}^-)}{\sqrt{\sum_{i \in l_{xy}} \left(r_{x,i} - r_{\bar{x}}^-\right)^2 + \sum_{i \in l_{xy}} (r_{y,i} - r_{\bar{y}}^-)^2}}$ ..... (8)

In Equation 8, the focus is on understanding the stochastic variation in selection and the potential decline in faith while managing the distributed system. To organise the combinations of factors or cases, we arrange them in space or time to maintain the historical pattern. This approach can be a limited arrangement of the multivariate traditional development of the data sets. It explains the covariances of the Gaussian Process (GP) in unpredictable components.

When the GP components are described, it refines the understanding based on the specified development. Gaussian Process Regression (GPR) should calculate the optimal limits of the probabilistic development across the entire dataset. This development is represented according to Brownian motion of $\{x(t), t \geq 0\}$ for the chosen requirement. The refined organisation of this is given by arrangement The K-th central view can be either limited or unlimited according to the laws of the distribution function.

DBC – Density-Based Cluster:

The process optimises memory usage to condense the region for space metrics. It involves measuring to segregate the lower-density regions while considering both supervised and unsupervised learning methods to identify distinctive groups. Within this contiguous group, the deviations of the function are classified according to binary values (Setosa, Virginica, Versicolor). The remaining parts do not associate with the contiguous group.

Unsupervised clustering, as outlined in Equation 9, is often employed during pre-processing based on certain axioms. This approach detects the nearest points to track cluster copies, such as T1 > T2. Distinctive values are used to identify errors, which indicate vulnerabilities in the processing; this tracking can help mitigate issues within the distributed system.

Additionally, hierarchical algorithms may be necessary to detect neighbourhoods, as seen in pre-clustering techniques.

$$\text{Simil}(x,y) = \cos(x^{\rightarrow}, y^{\rightarrow}) = \frac{x^{\rightarrow}.y^{\rightarrow}}{||x^{\rightarrow}||\,X||y^{\rightarrow}||} = \frac{\sum_{i\in l_{xy}} r_{x,i} r_{y,i}}{\sqrt{\sum_{i\in l_x} r_{x,i}^2}\sqrt{\sum_{i\in l_y} r_{y,i}^2}} \quad \text{..... (9)}$$

Filter Association:

Fig 3.3: Detecting fault-Tolerant

The CF has completed the work of advancing the significance of constraints from the left structure in evaluation techniques. It will differentiate between three methods that produce a higher degree of accuracy, performance, and data integrity. Refined datasets are utilised to calculate the processing needed to gather outcomes, which are then fed back into the distributed system. The goal was to improve the terminology and apply it to filter out errors and streamline the gaps in the combined structure. The recorded functions applied before processing, under the guidance of filtering techniques, aim to reduce redundancy and enhance the accuracy of the results. This evaluation uses methods such as Correlation Feature Selection (CFS), Best First Search, and Greedy Stepwise algorithms. Additionally, it includes enhanced screening to prevent malicious activities within the distributed system and addresses vulnerabilities related to data hacking and memory consumption over time.

- **CFS Subset Evaluation:** To assess the adequacy of future subset work in preparing datasets, we need to quantify certain elements. This involves identifying aspects that are currently irrelevant to the outcome. In addition to evaluating individual predictive capabilities, we must also consider the degree of redundancy among the factors. Even if refinement is not yet complete, we will emphasise the evaluation through cross-validation using k-fold methods.
- **BestFirst Search:** This technique involves backtracking to select attribute functions using greedy algorithms. If backtracking is employed, it helps detect harmful entries in the analysis state and addresses manipulations in accordance with consent monitoring. Blockchain methods can be used to prevent vulnerabilities and secure data functions. Each iteration of the attribute selection process is monitored to track the progress of refinement.
- **Greedy Step Wise:** This method focuses on forward and backwards searching within the space of selected attributes. It generates outcome measures that allocate specific regions in the distributed system. Without refining the subset of attribute selections, we may miss important evaluations.

4. RESULT AND DISCUSSION:

The Blockchain (BC) associated with ClustBigFim is utilised for attribute selection, classification, and evaluation refinement. BC plays a crucial role in ensuring the security of the distributed digital record system. Additionally, the classifiers are implemented to enhance data processing and performance efficiency. However, security remains a significant concern in these systems. Although decentralised recommenders can protect user privacy, they often lack the efficiency needed for widespread adoption. In this article, we utilise blockchain as the foundation for a decentralised collaborative filtering (CF) system, aiming to provide a broad range of features while simultaneously maintaining security. We propose a new architecture that incorporates blockchain alongside ClustBigFim and various recommendation stClustBigFIMailored according to how data is managed by users.

Table 4.1 evaluates training DatFig. 4 .1toComparisonhe miniFigure support for privacy prediction through secure access, while also identifyingoptimisation may arise during the manipulation of the monitoring distributed system.

Table ***4.1: Comparison with other Algorithms / Methods***

Dataset	Algorithm	Min. Support				
		100	**150**	**200**	**250**	**300**
	BigFIM	**56**	110	110	220	220
	ClustBigFIM	56	110	120	210	240
	Collaborative filtering	99	152	185	245	280



Fig4.1: Comparision Chart

Figure 4.1 illustrates the accuracy, performance, integrity, efficiency, and memory optimization alongside time management under various algorithms. It classifies and compares to identify the best solution within a big data system. Clustering defines the density and backtracking region, effectively managing attribute selection without redundancy before storage



Fig 4.2: Accuracy Ration for proposed BC with ClustBigFim

Figure 4.2 examines the accuracy ratio of the proposed techniques, which aim to provide an optimal solution. The statistical analysis includes minimum, maximum, Mean Absolute Error (MAE), Mean Squared Error (MSE), and time management related to security within big data. The results showed that our approach achieves accuracy comparable to unified methodologies, but with significantly higher efficiency, utilising a fully decentralised blockchain design. Additionally, our methods ensure client security.

5. CONCLUSION AND FUTURE ENHANCEMENT:

The blockchain platform offers a traceable and transparent environment, enabling trust-free transactions. In this research, a security management system has been successfully implemented based on a hybrid algorithm associated with blockchain technology. This system aims to deliver optimal solutions while ensuring accuracy, efficiency, performance, data integrity, fault tolerance, and the ability to detect and predict issues efficiently. The platform has deployed a statistically proven system across various fields using probabilistic ratios, providing recommendations to users effectively through the blockchain. By adopting multivariant approaches, the training data is enhanced via a digitally recorded distributed system. According to the models utilised, the blockchain interfaces with ClustBigFim to calculate and predict results by integrating various models into smart solutions. In the future, the proposed framework can accommodate different types of models with embedding tools, allowing for the simplification of data shapes and consequently reducing the overall data volume. Additionally, a reduction algorithm should be considered to streamline the similarity matrix. There is also an interest in investigating attribute selection through cross-validation of other smart functions and various recommendation algorithms.

REFERENCES:

1. Seo.D and Nam.H., "A parallel multi-channel cooperative spectrum sensing in cognitive radio networks," 2018 International Symposium on Antennas and Propagation, Busan, Korea (South), 2018, pp. 1-2.
2. Puppala.M, He.T, Yu. X, Chen.S, Ogunti. R, and Wong. S.T.C, "Data security and privacy management in healthcare applications and clinical data warehouse environment," in2016 IEEE-EMBS International Conference on Biomedical and Health Informatics (BHI), Feb 2016, pp. 5–8.
3. Stranieri. A Abawajy. J, Kelarev. A Huda.S, Chowdhury.M, and Jelinek. H.F, ''An approach for Ewing test selection to support the clinical assessment of cardiac autonomic neuropathy,'' Artif. Intell. Med., vol. 58, no. 3, pp. 185–193, Jul. 2013.
4. Victoria. L, Lemieux, 'Trusting records: is Blockchain technology the answer? Records Management Journal' 26(2):2016, pp. 110-139
5. Hammi, Mohamed Tahar, "Bubbles of Trust: A decentralized blockchain-based authentication system for IoT." Computers & Security 78 (2018): 126-142.
6. Zhonglin Chen, Shanzhi Chen, Hui Xu, Bo Hu, "A Security Scheme of 5G Ultra-Dense Network Based on Implicit Certificate," Wireless Communications and Mobile Computing, vol. 2018, no. 11, 23 May.2018.
7. Tipping. M.E., Sparse Bayesian learning, and the relevance vector machine. Journal of Machine Learning Research, 1:211–244, 2011.
8. Yanfang Le; Simon Fraser Univ., Burnaby, BC, Canada; Jiangchuan Liu; Ergun, F.; Dan Wang, "Online Load Balancing for MapReduce with Skewed Data Input" IEEE, pg 2004 - 2012.,2014
9. Satoshi Nakamoto, Bitcoin: A Peer-to-Peer Electronic Cash System, https://bitcoin.org/bitcoin.pdf [Accessed March 2017]
10. Marzouki. B, Driss. O.B, Ghdira. K, Multi-Agent model based on Chemical Reaction Optimization with Greedy algorithm for Flexible Job shop Scheduling Problem, Procedia ComputerScience 112 (2017) 81–90.
11. Manikandan D, Valliyammai C, Karthika RN, Blockchain-based Secure Big Data Storage on Cloud, International Journal of Recent Technology and Engineering (IJRTE) ISSN: 2277-3878, Volume-9 Issue-4, November 2020.
12. S. Dhanalakshmi, G.Charles Babu, An Examination Of Big Data And Blockchain Technology, International Journal of Innovative Technology and Exploring Engineering (IJITEE) ISSN: 2278-3075, Volume-8 Issue-11, September 2019.
13. Alex. R. Mathew, Cyber Security through Blockchain Technology, International Journal of Engineering and Advanced Technology (IJEAT) ISSN: 2249 – 8958, Volume-9 Issue-1, October 2019.

14. Dong Wang, Huanjuan Wang & Yuchen Fu, Blockchain-based IoT device identification and management in 5G smart grid, EURASIP Journal on Wireless Communications and Networking volume 2021, Article number: 125 (2021).
15. Swagatika Sahoo, Rishu Roshan, Vikash Singh, and Raju Halder, BDmark: A Blockchain-driven Approach to Big Data Watermarking, ACIIDS, 2020.